

PRODUCT SPECIFICATIONS

HWB700/HWB700HB Radiant Wood Burning



INTERIOR DIMENSIONS

Front opening width: 44"

Front opening height: 27"

Rear wall width: 34"

Firebox depth: 22"

TECHNICAL INFORMATION

Flue Series (Std.): "L" Series Double Wall

Flue Size: 11" Inner; 13" Outer

Clearance to Flue: 2"

Firestop Framing: 17" x 17"

Minimum Flue Height: 15'

Maximum Flue Height: 86'

Minimum Height with 2 Elbows: 15'

Minimum Height with 4 Elbows: 21'

Clearance to Fireplace: 1-1/2"

Minimum Hearth Size (D x L): 20" x 68"

UL Design Certified

FACTORY INSTALLED OPTIONS

Refractory firebrick: SB5400



Refractory Herringbone firebrick: SB5400HB

FIELD INSTALLED ACCESSORIES


Glass Doors: GDB54 (Black), GDPB54 (Polished Brass), GD54SS (Stainless)

Outside Air Kit: AK4, FP4U, 403

Terminations(Std.): "L" Series LC, LCL, CF11, SQ8, LFSQT, LPC



FRONT VIEW



SIDE VIEW

Framing dimensions in illustrations accommodate 1/2" finishing material.

* HB=Herringbone brick pattern.



A Brand of Monessen Hearth Systems Co.
149 Cleveland Drive, Paris, Kentucky 40361

www.monessenhearth.com



To avoid personal injury or property damage, the product described by this brochure must be installed, operated and maintained in strict compliance with the instructions packaged with the product and all applicable building or fire codes. Contact local building or fire officials about restrictions and installation inspection requirements. All photographs and drawings on this brochure are for illustrative purposes only and are not intended for, nor should they be used as a substitute for the instructions packaged with the unit. Appearance and specifications of the product are subject to change without notice. © 2007 Monessen Hearth Systems Co.